SAFETY DATA SHEET

PRODUCT NAME: DIAMOND (PCD: Polycrystalline Diamond) Tools

1. Identification of the Substance and of the Company

1-1. Product Identifier :

DIAMOND (PCD: Polycrystalline Diamond) Tools and Cemented carbide (Base Insert) (hereinafter referred to "PCD/Cemented Carbide")

1-2. Company Information

ompany mornation					
Manufacturer	: Kyocera Corporation				
Address	: 6 Takeda Tobadono-Cho,	Fushimi-Ku K	(yoto 612-8501		
Division	: Corporate Cutting Tool Gr	oup			
Phone No.	: +81-75-604-3651	FAX No.	: +81-75-604-347	2	
Emergency Contact	: Sendai Quality Assuran	ce Section ((Sendai Plant)	Phone No.	: +81-996-23-4116

1-3. Recommended use and Restriction on use :

Cutting tools for mainly metal materials

1-4. Attention to the Phase/State of the PCD/Cemented Carbide

- PCD/Cemented Carbide as solid state like cutting tools is chemically stable and safe at explosive, flammable, combustible, pyrophoric, water-reactive, and oxidizability under normal environment.
- PCD/Cemented Carbide are safe for use as the cutting tools (grinding, machining, rolling for metals) under normal condition.
- This SDS informs about the dust, fume or vapor which occur from PCD/Cemented Carbide producing process such as raw material powder handling and grinding.

2. Hazard Identification

2-1. GHS Classification

Some data (such as the burning rate test data, etc.) for the dust, fume or vapor which occur from PCD/Cemented Carbide producing process are unavailable. Therefore, they are not be classified by GHS.

In here, GHS classification of the each metallic ingredient (cobalt, nickel and chromium) for composing the PCD/Cemented Carbide can be disclosed. In addition, other hazards and harmful effects (for health, environment, physical and chemical) which are not listed are unclassifiable or non-applicable by GHS.

GHS classification for the hazards of cobalt alone in below,

(When cobalt is included as ingredients of PCD/Cemented Carbide.)

	ed as ingredients of redreemented carbide:)	
Health Hazard	 Respiratory sensitization 	Category1
	 Skin sensitization 	Category1
	Carcinogenicity	Category2
	Reproductive toxicity	Category2
	 Specific target organ toxicity 	Category3
	(Single exposure)	(Respiratory tract irritation)
	 Specific target organ toxicity 	Category1
	(Repeated exposure)	(Respiratory)
Environmental	 Hazardous to the aquatic environment 	Category4
Hazard:		

GHS classification for the hazards of nickel alone in below,

(When nickel is included as ingredients of CBN/Cemented Carbide.)

Health Hazard	Respiratory sensitization	Category1
	Skin sensitization	Category1
	Carcinogenicity	Category2
	Specific target organ toxicity	Category1
	(Single exposure)	(Respiratory tract irritation)
	Specific target organ toxicity	Category1
	(Repeated exposure)	(Respiratory)
Environmental	 Hazardous to the aquatic environment 	Category4
Hazard:		

GHS classification for the hazards of chromium alone in below, (When chromium is included as ingredients of CBN/Cemented Carbide.)

	sinded as ingredients of CDM/Certiented Carbide	•/
Health Hazard	 Serious eye damage 	Category2B
	 Respiratory sensitization 	Category1
	Skin sensitization	Category1
	 Germ cell mutagenicity 	Category2
	 Specific target organ toxicity 	Category2
	(Single exposure)	(Respiratory tract irritation)
	 Specific target organ toxicity 	Category3
	(Repeated exposure)	(Respiratory)

2-2. GHS Label Elements

GHS label elements of the each metallic ingredient (cobalt) for composing the PCD /Cemented Carbide can be disclosed in below.

	Cobalt	Nickel	Chromium
Hazard Pictograms :	<		
Signal Words:		Danger	
Hazard Statements :	 Risk of causing allergies, asthma or breathing difficulties if inhaled. Risk of causing an allergic skin reaction. May cause cancer. May cause adverse effects on fertility or the unborn child. Risk of respiratory irritation. Cause of respiratory failure due to long-term or repetitive exposure. May be harmful to aquatic life due to long-term effects 	 Risk of causing allergies, asthma or breathing difficulties if inhaled. Risk of causing an allergic skin reaction. May cause cancer. Respiratory and kidney disorders Cause of respiratory failure due to long-term or repetitive exposure. May be harmful to aquatic life due to long-term effects 	 Risk of causing allergies, asthma or breathing difficulties if inhaled. Risk of causing an allergic skin reaction. Suspected of causing genetic disease Failure to systemic toxicity Risk of respiratory irritation.

Precautionary	[Prevention]
Statements :	Obtain safety instructions* before use.
	• Do not handle until all safety precautions have been read and understood.
	• Use appropriate personal protection and ventilation system keeping away from
	exposure.
	Wear suitable protective gloves.
	 When insufficient ventilation, wear respirator as required.
	Do not breathe dust, fume or vapor.
	 Do not eat, drink or smoke in handling area.
	Wash skin thoroughly after handling.
	Do not release into the environment.
	[Responses]
	· If inhaled, move to fresh air and take a rest with posture easy to breathe.
	 If respiratory symptoms occurs, contact a doctor.
	When feeling ill, get medical advice/attention.
	Take off contaminated clothing and wash before reuse.
	 If on skin, rinse away immediately with a large amount of water and soap.
	 If skin irritation occurs, contact a doctor and get medical advice/attention.
	 If exposed or concerned, get medical advice/attention.
	• If dust is in eyes, immediately wash away with clean water (remove the contact lenses
	if possible). If irritation persists, get medical advice/attention.
	·If a large amount of dust is swallowed, get medical advice/attention after ingesting
	plenty of water to dilute.
	[Storage]
	 Avoid sudden changes of temperature and high humidity for storage.
	[Disposal]
	·Dispose of contents/container to an approved waste disposal plant under the laws.

*For safety instructions, refer to the Japan Cutting & Wear-resistant Tool Association website (<u>http://www.jta-tool.jp/</u>) .

3. Composition/Information on Ingredients

- Distinction between substance and mixture: Mixture (alloy)
- Ingredients and concentration or concentration range (composition) of the PCD/Cemented Carbide.

Ingredient	Chemical Formula	CAS#	Official Number ,Law for PRTR*	Industrial Safety and Health Law(Official Number)	Composition mass%
PCD layer and Cemented Car	bide layer				
Synthetic diamond	C	7782-40-3	N/A	N/A	3095
Tungsten Carbide	WC	12070-12-1	N/A	N/A	070
Cobalt	Со	7440-48-4	Class 1:132	Appendix 9-172	1030
Junction layer					
Silver	Ag	7440-22-4	Class 1:82	Appendix 9-137	2060
Copper	Cu	7440-50-8	N/A	Appendix 9-379	1550
Nickel	Ni	7440-02-0	Class 1:308	Appendix 9-418	010
Cemented Carbide(Base Insert)					
Tungsten Carbide	WC	12070-12-1	N/A	N/A	8595
Cobalt	Со	7440-48-4	Class 1:132	Appendix 9-172	515
Titanium Carbide	TiC	12070-08-05	N/A	N/A	010
Vanadium carbide	VC	12070-10-9	Class1:321	N/A	05
Chromium	Cr	7440-47-3	Class 1: 87	Appendix 9-142	05
Nickel	Ni	7440-02-0	Class1:308	Appendix9-418	05

*Law for PRTR: Law concerning Reporting, etc. of Releases to the Environment of Specific Chemical Substances and Promoting Improvements in Their Management.

• For the details regarding the content of the designated chemical material such as cobalt, nickel, and chromium, and vanadium carbide (effective digit: 2), please contact the above address.

4. First-Aid Measures

Inhalation:

- If the high concentration of dust is inhaled or respiratory symptoms (coughs, gasping, shortness of breath, etc.) are experienced, move to fresh air and take a rest with posture easy to breathe. If breathing difficulties occur, administer oxygen inhalation. If breathing has stopped, immediately administer artificial respiration and get medical advice/attention.
- If irritation or rash persists, get medical advice and attention.

Skin Contact:

- If dust is contacted with skin, take off contaminated clothing and rinse the affected area with soapy water thoroughly.
- If irritation or rash persists, get medical advice/attention.

Eye Contact

- If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible).
- If irritation persists, get medical advice/attention.

Ingestion

• If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute.

5. Fire-Fighting Measures

Extinguishing Media

• To extinguish the fire of dust, use dry sand, expanded vermiculite, dilatable perlite, ABC type (general, oil, electric fire) powder extinguishers or water (no water allowed for the dust containing cut powders of light metal such as magnesium and aluminum).

Special Protective Actions for Fire-Fighters

• In fighting a fire, wear a protective clothing, dust-proof respirator or respiratory protective equipment

6. Accidental Release Measures

Personal Precautions

• It is recommended that someone who cleans dust should wear clothing and respiratory protective equipment to minimize exposure.

Environmental Precautions

• Dispose of dust as industrial wastes and prevent release in water systems.

Containment and Cleanup Methods and Equipment

 If there is dust which occur from Cemented Carbide producing process, isolate the area and remove with a cleaner equipped with a filter which can take up fine particles very efficiently. If appropriate removing methods are not available, sweep with water sprayers or wet mops.

7. Handling and Storage

Handling

- If the disperse of dust containing cobalt is concerned, provide local exhaust ventilation and use personal protective equipment to minimize exposure to human body.
- Obtain safety instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust, fume or vapor.
- Do not eat, drink or smoke in handling area.
- Wash skin thoroughly after handling.
- Do not release into the environment.

Storage

• Avoid sudden changes of temperature and high humidity for storage.

8. Exposure Controls/Personal Protection

Exposure Prevention

· Permissible concentration in working environment (reference value)

Ingredient	Chemical Formula	OSHA*PEL* mg/m ³ (Metal dust concentration)	ACGIH*TLV* mg/m ³ (Metal dust concentration)	JSOH*OEL* mg/m ³ (Respirable dust conc.)
PCD layer and Cemented Carbide layer				
Synthetic diamond	С	N/A	N/A	N/A
Tungsten Carbide	WC	5 (as W)	5 (as W)	N/A
Cobalt	Со	0.1	0.02	0.05
Vanadium carbide	VC	N/A	N/A	N/A
Nickel	Ni	1	1.5	1.0
Chromium	Cr	1	0.5	0.5

* OSHA: Occupational Safety & Health Administration U.S. Department of Labor

* PEL: Permissible Exposure Limit

* ACGIH: American Conference of Governmental Industrial Hygienists Inc.

- * TLV: Threshold Limit Value
- *JSOH: Japan Society for Occupational Health
- *OEL: Occupational Exposure Limit
- * N/A: Not Applicable

Facility measures

Provide local exhaust ventilation so that dusts in the air may not exceed the exposure limits in the above table. It is to be noted that management concentration of the cobalt (and its inorganic compounds) is to be 0.02mg/m3 in accordance with the working environment assessment standard by Japanese Minister of Health, Labour and Welfare under the paragraph (2), Article 65-2 of the Industrial Safety and Health Act in Japan.

In addition, cobalt (and its inorganic compounds) in the storage or handling, and that to take the necessary action conforming to the Ordinance on Prevention of Hazards due to Specified Chemical Substances.

Protection Measures

• Respiratory Protection: Dust-proof respirators and respiratory protective equipment are recommended.

Protective glasses for dust are recommended.

- Hand Protection: Protective gloves for dust are recommended.
- Eye Protection:
- Skin/Body Protection: Avoid direct skin contact.

Clean up deposited dust on clothing, rags, etc. by washing or absorbing with suitable filters but not by whisking off. Change the contaminated clothing into clean one.

Hygiene Measure

Wash skin thoroughly after handling.

9. Physical and Chemical Properties

Appearance:	Dark gray color
	(In case of the coated or surface treated cemented carbide, the appearance color is
	often different.)
Odor:	Odorless
pH:	No data available
Melting Point:	No data available
Boiling Point:	No data available
Flash Point:	No data available
Vapor Pressure:	No data available
Specific Gravity:	11.0 - 15.5
Solubility:	Insoluble

10. Stability and Reactivity

A grain of dust which occur from PCD/Cemented Carbide producing process is very fine and under the specific conditions in which the dusts are mixed with grinding oil with low flash point, it is possible to become pyrophoric. If dusts under very flammable conditions are dispersed in the air, it is possible to explode.

The each metallic ingredient (cobalt) for composing the PCD/Cemented Carbide has the following information about stability and reactivity under specific conditions.

Stability and reactivity of cobalt alone in below, (When cobalt is included as ingredients of PCD/Cemented Carbide.) Stable to heat and contact with water Stability: Ignite spontaneously in air Hazardous reactions: It reacts with strong oxidizing agents It reacts violently with oxygen, and it poses a risk of fire or explosion It reacts violently with acid to generate hydrogen Contact with incompatible materials Conditions to avoid: Strong oxidizing agents, acid Incompatible materials: Hazardous decomposition products: By combustion, cobalt oxide and fumes of cobalt oxide may occur **Toxicological Information** 11. Acute Toxicity: No data available on PCD/Cemented Carbide Skin Corrosion/Irritation: No data available on PCD/Cemented Carbide Serious Eye Damage/Eye Irritation: No data available on PCD/Cemented Carbide **Respiratory or Skin Sensitization:** No data available on PCD/Cemented Carbide Germ Cell Mutagenicity: No data available on PCD/Cemented Carbide Carcinogenicity: Group 2A on IARC, as cobalt powder coexisting with tungsten carbide powder. Suspected to be carcinogenic in humans (Ref.1) No data available on PCD/Cemented Carbide **Reproductive Toxicity:** Specific Target Organ Toxicity/Systemic Toxicity: No data available on PCD/Cemented Carbide (Single Exposure) Specific Target Organ Toxicity/Systemic Toxicity: No data available on PCD/Cemented Carbide (Repeated Exposure) Aspiration Hazard: No data available on PCD/Cemented Carbide **Ecological Information**

12.

The aquatic environment acute hazard

- Not reported on PCD/Cemented Carbide
- The aquatic environment chronic hazard
 - Not reported on PCD/Cemented Carbide

Mobility

• Not reported on PCD/Cemented Carbide

13. WASTE DISPOSAL PRECAUTIONS

Safe and environmentally desirable disposal method

- The main ingredients such as tungsten carbide, cobalt are rare metal. It is desirable to collect and recycle them.
- For disposal, conform to the applicable laws regarding industrial wastes such as 'Waste Disposal and Public Cleansing Law' and relevant local by laws.

14. Transport Information

International Regulations

0	
UN Number:	Not applicable
UN Hazard Class:	Not applicable
Marine Pollutant:	Not applicable

*When transporting a powder of metallic ingredients (cobalt) for composing the PCD/Cemented Carbide, there is a possibility that it is necessary to take appropriate action in accordance with the relevant provisions established by IMO (International Maritime Organization), ICAO (International Civil Aviation Organization), IATA (International Air Transport Association).

Domestic Regulations

Land Regulatory Information	Not applicable
UN Number:	Not applicable
UN Hazard Class:	Not applicable
Marine Pollutant:	Not applicable

*When transporting a powder of metallic ingredients (cobalt) for composing the PCD/Cemented Carbide, there is a possibility that it is necessary to take appropriate action in accordance with the relevant provisions of Ship Safety Law and the Aviation Law.

Special Safety Measures

When transporting the dust which occur from PCD/Cemented Carbide producing process, make sure that there is no damage or corrosion or leakage of the container, to ensure implementation of the prevention of collapse of cargo.

15. Regulatory Information

Law for Pollutant Release and Transfer Register (PRTR)

Cobalt	:	"Class 1 designated chemical substances", Cabinet Order No.132
Vanadium carbide	:	"Class 1 designated chemical substances", Cabinet Order No.321
Nickel	:	"Class 1 designated chemical substances", Cabinet Order No.308
Chromium	:	"Class 1 designated chemical substances", Cabinet Order No.87

 Industrial Safety and Health Law, Ordinance on Prevention of Hazards due to Specified Chemical Substances Cobalt: The substances are defined in the Article 57-2 of the Act, and the cobalt is listed by No.172 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names. etc."

Article 2, Paragraph 1, Items 2 and 5 of Ordinance on Prevention of Hazards due to Specified Chemical Substance, Specified chemical substance class 2, Management class 2.

When the content of cobalt and cobalt oxide is less than 1%, the Ordinance on Prevention of Hazards due to Specified Chemical Substance is not covered.

- Nickel: The substances are defined in the Article 57-2 of the Act, and the nickel is listed by No.418 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Chromium: The substances are defined in the Article 57-2 of the Act, and the chromium is listed by No.142 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."

In other region, follow the local regulations.

16. Other Information

Other Hazardous Information

The following attention should be paid for dust which occur from PCD/Cemented Carbide producing process.

- If a large amount of dust containing cobalt is inhaled, blood, heart, thyroid gland, and spleen disorders may result. (Ref.2)
- It is reported that repeated or prolonged contact with cobalt, nickel, or chromium may affect skin, respiratory organs, heart, etc. (Ref.3 - 6)
- For carcinogenicity of metallic ingredients of CBN/Cemented Carbide has the following knowledge.

Cobalt metal	ACGIH	A3: Confirmed animal carcinogen with unknown
		relevance to humans.
	IARC	2B: Possibly carcinogenic to humans.
	Japan Society for	2B: The substance has been determined to be possibly
	Occupational Health	carcinogenic to humans (with relatively insufficient
		evidence).
Nickel metal	ACGIH	A5: Not suspected as a human carcinogen.
	IARC	2B: Possibly carcinogenic to humans.
	Japan Society for	2B: The substance has been determined to be possibly
	Occupational Health	carcinogenic to humans (with relatively insufficient
		evidence).
Chromium metal	IARC	3: Not classifiable as to its carcinogenicity to humans.

- *ACGIH : American Conference of Governmental Industrial Hygienists Inc.
- *IARC : International Agency for Research on Cancer

Disclaimer

Although Kyocera has attempted to provide current and accurate information herein, Kyocera makes no representations regarding the accuracy or completeness of the information and assumes no liability for any loss, damage, or injury of any kind which may result from or arise out of the use of or reliance on the information by any person. Numerical values, such as content, physics/chemical property, are not guaranteed values.

Reference URI

•	Ministry of Economy, Trade and Industry:	http://www.meti.go.jp/
•	Ministry of the Environment :	http://www.env.go.jp/
•	Ministry of Health, Labour and Welfare :	http://www.mhlw.go.jp/
•	Japan Industrial Safety and Health Assoc. :	http://www.jaish.gr.jp/
•	International Agency for Research on Cancer :	http://monographs.iarc.fr/
•	International Chemical Safety Card :	http://www.nihs.go.jp/ICSC/
•	National Institute of Technology and Evaluation:	http://www.safe.nite.go.jp/ghs/list.html

References Documents

- (1) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, vol.86 (2006).
- (2) Food & Drug Research Laboratories, study No.8005B (4.11.84).
- (3) Shirakawa et al., Chest. 95, 29 (1989).
- (4) International Chemical Safety Cards (cobalt, chromium, nickel).
- (5) The Guide to Chemical Hazards (edited by Japan Industrial Safety & Health Association)
- (6) A. O. Bech et al., Brit. J. Ind., 19, 239 (1962)