

Tangential 90° End Mill with 4-Edge Inserts

MA90



Reliable, Stable, High Quality Machining with Extended Tool Life

Unique tangential 90° end mill design provides a large variety of machining operations

Newly designed inserts with grade PR18 series coating technology
High quality surface finish and excellent wall accuracy

Supports multi-functional machining
such as 3D milling



Tangential 90° End Mill with 4-Edge Inserts

MA90

Original tangential 90° end mill with economical 4-edge inserts. New grade PR18 Series and unique insert cutting edge design creates high-quality machining with longer tool life

1 The MA90 tangential end mills provide a large variety of machining operations

Challenges

Conventional end mill

- Sudden fractures can cause damage to the holder
- Insert defects preventing use of all four corners

Tangential end mill

- Premature tool wear can quickly deteriorate the surface finish quality
- Poor wall accuracy

SOLUTION

Kyocera's MA90 tangential end mill solves these problems with a unique insert shape and PR18 Series grade technology.

Large web thickness

High rigidity

Peripheral grinding specifications

Excellent wall accuracy

Special wiper edge

Large relief angle suppresses wear
High-quality surface finish



Reliable tooling brings peace of mind to machinists.



Multifunctional (G-class insert)

Supports three-dimensional machining

Unique cutting edge design

Excellent fracture resistance and low cutting force design

Newly developed insert grade

MEGACOAT NANO EX

PR18 Series delivers longer tool life

2

New insert grade PR18 Series provides a significantly longer tool life

Next-generation insert grade for milling

NEW

PR18 Series

Kyocera's Nano Layer Coating Technology

Longer Tool Life with Next-generation Coating for Milling




MEGACOAT
NANO EX | Milling |

Double Lamination Technology Maintains Longer Tool Life

Multi-layer structure with two unique nano layers
Superior abrasion resistance and fracture resistance

Special Nano Layer x Multilayer Lamination


Nano-Layer



AlCr-based coating
with excellent abrasion resistance

High toughness
suppresses crack growth

Nano-Layer



AlTi-based coating
with excellent heat resistance

High toughness
suppresses crack growth

Multi-layering of high-performance nano layers
Increases toughness with suppression of crack growth and optimization of internal stress

CG Image


Extensive lineup of insert grades covers a variety of machining materials and applications

Workpiece material	P Steel					M Stainless steel					K Cast iron				
	01	10	20	30	40	01	10	20	30	40	01	10	20	30	40
Lineup	1st recommendation PR1825					1st recommendation PR1835					1st recommendation PR1810				
	Wet PR1835					High-speed machining CA6535									
H Hardened material	PR015S (GH)					S Heat-resistant alloy					Titanium alloy PR1835				


PR1825 Wear resistance comparison (Internal evaluation) V-T graph

Life criteria:
Flank face wear = 0.10 mm

Cutting conditions:
Vc = **160 / 300** m/min
ap × ae = 2.0 × 110 mm, fz = 0.12 mm/t
SCM440 Dry
PNMU1205ANER-GM (MFPN)




Coating characteristics (Internal evaluation)



MEGACOAT NANO EX | Milling

Oxidation progression comparison (Internal evaluation)


Suppresses oxidation progression with excellent oxidation resistance



*Section after holding at 1,200 degrees for 30 minutes in air

Coating layer toughness evaluation (Internal evaluation)

Excellent coating toughness with small crack length



*Micro-Vickers measurement

3

Achieve reliable results with an insert shape designed for high quality machining and long tool life

Unique cutting edge design delivers high fracture resistance and low cutting forces

Special wiper edge and peripheral grinding specifications provide high quality finish and long tool life



Advantage

Both the A.R. and the relief angle of the wiper edge are large.
Low resistance and excellent surface finish



Unique cutting edge design

Superior fracture resistance and low cutting force



Special wiper edge

Large relief angle: Excellent surface finish and wear suppression
Stepped corners: Designed to prevent seat damage


Excellent

Excellent surface finish >>>


Special wiper edge design suppresses abrasion progress of the edge. Maintains high-quality finished surface

Wear and Surface Finish Comparison (Internal evaluation)

Wiper edge wear



Surface finish roughness (Bottom surface)



Cutting conditions: $V_c = 200$ m/min, $a_p \times a_e = 1 \times 37.5$ mm, $f_z = 0.1/0.12$ mm/t, Dry S50C $\Phi 50$ (6/7 inserts) BT50

Excellent wall accuracy


Excellent

Peripheral grinding specifications

Unique, sloped, edge shape
Grounded peripheral provides higher precision



Wall accuracy comparison (Internal evaluation)



Cutting conditions: $V_c = 150$ m/min, $a_p \times a_e = 3 \times 5$ mm 4 passes, $f_z = 0.1$ mm/t, Dry S50C Dia.20 (3 inserts) BT50

>>> Long tool life and high-speed machining

Test 1

Even if the main cutting edge is in good condition, the tool reached the end of life due to deterioration of the finished surface.

MA90



Test 2


Machined with reduced cutting speed because the surface finish deteriorated early.

MA90



Edge condition and finished surface

		MA90	Competitor E Tangential	Competitor F Tangential
Wiper edge	After 3.8 min			
	After 6.5 min			
Main cutting edge		Abrasion progress: Small Good	Wear progress: Large Spark generation Good	Wear progress: Large Spark generation Good
Finished surface	After 13.1 min	Good 8.0µmRz (1.3µmRa)	Cloudy finish 20.6µmRz (2.2µmRa)	Surface finish deteriorating 14.9µmRz (3.0µmRa)
	Results	Main cutting edge: Good Wiper edge wear: Small wear Good finished surface and can continue to use	Main cutting edge: Good Wiper edge wear: Progressive Worse finished surface	Main cutting edge: Good Wiper edge wear: Progressive Worse finished surface



Toolholder Dimensions 09 Size (LOGU09 ...)

Description	Stock	Number of Inserts	Dimensions (mm)					Coolant hole	Shape	Weight	Maximum number of revolutions (min ⁻¹)
			DC	DCON	LF	LH	APMX				
Standard shank	●	2	16	12	100	23	8	Yes	Fig.1	0.1	29,500
			18S16-09T2C	18							16
	●	3	20	16	110	26				0.2	26,600
	22S20-09T3C		22	20	25,400						
	25S20-09T3C		25	20	23,900						
	●	4	25	20	120	29				0.3	23,900
	25S20-09T4C	25	20	22,600							
	●	3	28	25	120	29				0.3	23,900
	28S25-09T3C	28	25	130	32	0.5				21,900	
	●	4	30	25	130	32				0.5	21,200
	30S25-09T4C	30	25	130	32	0.5				21,200	
	●	5	32	25	150	50				0.9	20,300
	32S25-09T5C	32	25	150	50	0.9				20,300	
	●	4	35	32	150	50				1.0	19,000
	35S32-09T4C	35	32	150	50	1.0				19,000	
●	5	35	32	150	50	0.9	17,000				
35S32-09T5C	35	32	150	50	0.9	17,000					
●	4	40	32	120	40	0.9	17,000				
40S32-09T4C	40	32	120	40	0.9	17,000					
●	6	40	32	120	40	0.9	17,000				
40S32-09T6C	40	32	120	40	0.9	17,000					
●	5	50	32	120	40	0.9	17,000				
50S32-09T5C	50	32	120	40	0.9	17,000					
●	7	50	32	120	40	0.9	17,000				
50S32-09T7C	50	32	120	40	0.9	17,000					
Same size shank	●	2	16	16	100	26	8	Yes	Fig.2	0.1	29,500
			20S20-09T2C	20	20	110					30
	●	3	20	20	110	30				0.4	23,900
	20S20-09T3C		20	20	110	30					
	25S25-09T3C		25	25	120	32					
	●	4	25	25	120	32				0.7	21,200
	25S25-09T4C		25	25	120	32					
●	5	32	32	130	40	0.7	21,200				
32S32-09T4C		32	32	130	40						
●	5	32	32	130	40	0.7	21,200				
32S32-09T5C		32	32	130	40						
Long shank	●	2	20	18	150	30	8	Yes	Fig.1	0.3	26,600
			20S20-09T2CL	20		20					
	●	2	25	25	170	50			Fig.2	0.6	23,900
	25S25-09T2CL		25	25		50					
●	2	32	32	200	65	Fig.2	1.1	21,200			
32S32-09T2CL		32	32		65						

Maximum number of revolutions

Set the number of revolutions per minute within the recommended cutting speed specified by the workpiece on Page 12.

Do not use the end mill or cutter at the maximum revolution or higher since the centrifugal force may cause chips and parts to scatter even under no load.

●: Standard Stock

Toolholder Dimensions 12 Size (LOGU12 ...)

Description		Stock	Number of Inserts	Dimensions (mm)					Coolant hole	Shape	Weight	Maximum number of revolutions (min ⁻¹)						
				DC	DCON	LF	LH	APMX										
Standard shank	MA90 -	25S20-12T2C	●	2	25	20	120	29	12	Yes	Fig.1	0.3	18,300					
		28S25-12T2C	●		28	25						130	32	0.4	17,300			
		30S25-12T2C	●	3	30		150	50						0.5	16,800			
		30S25-12T3C	●		32	32						40	16,300					
		32S25-12T2C	●	3	35		120	40						0.9	15,600			
		32S25-12T3C	●		40	32						120	14,600					
		35S32-12T3C	●	4	40		120	40						0.8	13,100			
		40S32-12T3C	●			50						32	120			40		
		40S32-12T4C	●	6	50	120	40	0.8						13,100				
		50S32-12T4C	●									6	50		120	40	0.8	13,100
50S32-12T6C	●	6	50	120	40	0.8	13,100											
Same size shank	MA90 -							25S25-12T2C	●	2	25	25	120	32	12	Yes	Fig.2	0.4
		32S32-12T2C	●	32	32	130	40	0.7	16,300									
		32S32-12T3C	●	3	12	Yes	Fig.2			0.6	18,300							
Long shank	MA90 -	25S25-12T2CL	●	2				25	25			170	50	12	Yes	Fig.2	1.1	16,300
		32S32-12T2CL	●					32	32			200	65					





Maximum number of revolutions


● Standard Stock

Set the number of revolutions per minute within the recommended cutting speed specified by the workpiece on Page 12.

Do not use the end mill or cutter at the maximum revolution or higher since the centrifugal force may cause chips and parts to scatter even under no load.

Parts / Applicable Inserts

Description			Clamp screw	Wrench	Anti-seizure compound	Arbor bolt	
							
09 Size (LOGU09...)	End Mill Modular	MA90-16...-09...	SB-44865UTRP	DTPM-8	P-37	-	
		MA90-18...-09...	Tightening torque for clamping insert 1.2 N·m			-	
		MA90-20~50...-09...				-	
	Face Mill	MA90-040R-09...	SB-44880UTRP	DTPM-8		HH8×25	
		MA90-050R-09...	Tightening torque for clamping insert 1.2 N·m			HH10×30	
		MA90-063R-09...					
12 Size (LOGU12...)	End Mill Modular	MA90-...-12...			P-37	-	
	Face Mill	MA90-040R-12...-M				HH8×25	
		MA90-050R-12...-M				HH10×30	
		MA90-063R-12...-M				HH12×35	
		MA90-080R-12...-M	SB-40104TRP	DTPM-15		Tightening torque for clamping insert 3.5 N/m	-
		MA90-100R-12...-M					-
		MA90-125R-12...-M				HH12×35	
		MA90-080R-12...				-	
		MA90-100R-12...				-	
MA90-125R-12...			-				



Toolholder dimensions 09 size (LOGU09...)


Description	Stock	Number of Inserts	Dimensions (mm)											Coolant hole	Shape	Weight (kg)	Maximum number of revolutions (min ⁻¹)	
			DC	DCSFMS	DCB	DCCB ₁	DCCB ₂	LF	CDBP	KDP	KWW	APMX						
Metric Spec	MA90 -	040R-09T4C-M	●	4	40	38	16	15	9	40	19	5.6	8.4	8	Yes	Fig.1	0.2	26,600
		040R-09T6C-M	●	6														
		050R-09T5C-M	●	5	50	48	22	18	11	21	6.3	10.4	0.4	23,900				
		050R-09T7C-M	●	7														
		063R-09T6C-M	●	6	63	0.5	21,200											
		063R-09T9C-M	●	9														

Maximum number of revolutions ●: Standard Stock
 Set the number of revolutions per minute within the recommended cutting speed specified by the workpiece on Page 12.
 Do not use the end mill or cutter at the maximum revolution or higher since the centrifugal force may cause chips and parts to scatter even under no load.

Toolholder dimensions 12 size (LOGU12...)

Description	Stock	Number of Inserts	Dimensions (mm)											Coolant hole	Shape	Weight (kg)	Maximum number of revolutions (min ⁻¹)	
			DC	DCSFMS	DCB	DCCB ₁	DCCB ₂	LF	CDBP	KDP	KWW	APMX						
Metric Spec	MA90 -	040R-12T3C-M	●	3	40	38	16	14	9	40	19	5.6	8.4	12	Yes	Fig.1	0.2	14,600
		040R-12T4C-M	●	4														
		050R-12T4C-M	●	5	50	48	22	18	11	21	6.3	10.4	0.3	13,100				
		050R-12T6C-M	●	6														
		063R-12T6C-M	●	6	63	0.4	11,700											
		063R-12T8C-M	●	8														
		080R-12T7C-M	●	7	80	70	27	20	13	50	24	7	12.4	1.2	10,400			
		080R-12T10C-M	●	10														
		100R-12T9C-M	●	9	100	78	32	45	-	63	30	8	14.4	1.5	9,300			
		100R-12T13C-M	●	13														
		125R-12T12C-M	●	12	125	89	40	55	-	63	33	9	16.4	2.5	8,300			
		125R-12T16C-M	●	16														
Bore Dia. Inch Spec	MA90 -	080R-12T7C	●	7	80	70	25.4	20	13	50	27	6	9.5	12	Yes	Fig.1	1.2	10,400
		080R-12T10C	●	10														
		100R-12T9C	●	9	100	78	31.75	45	-	63	34	8	12.7	1.5	9,300			
		100R-12T13C	●	13														
		125R-12T12C	●	12	125	89	38.1	55	-	63	38	10	15.9	2.6	8,300			
		125R-12T16C	●	16														

Maximum number of revolutions ●: Standard Stock
 Set the number of revolutions per minute within the recommended cutting speed specified by the workpiece on Page 12.
 Do not use the end mill or cutter at the maximum revolution or higher since the centrifugal force may cause chips and parts to scatter even under no load.



Toolholder dimensions 09 size (LOGU09...)

Description	Stock	Number of Inserts	Dimensions (mm)							Coolant hole	Maximum number of revolutions (min ⁻¹)	
			DC	DCSFMS	DCON	OAL	LF	CRKS	H			APMX
MA90 - 20M10-09T2C	●	2	20	18.8	10.5	48	30	M10×P1.5	15	8	Yes	19,000
20M10-09T3C	●	3										
25M12-09T3C	●	4	25	23	12.5	56	35	M12×P1.75	19			17,000
25M12-09T4C	●											
32M16-09T4C	●	5	32	30	17	62	40	M16×P2.0	24			15,100
32M16-09T5C	●											

● Standard Stock

Toolholder dimensions 12 size (LOGU12...)

Description	Stock	Number of Inserts	Dimensions (mm)							Coolant hole	Maximum number of revolutions (min ⁻¹)	
			DC	DCSFMS	DCON	OAL	LF	CRKS	H			APMX
MA90 - 25M12-12T2C	●	2	25	23	12.5	56	35	M12×P1.75	19	12	Yes	18,300
32M16-12T2C	●		32	30	17	62	40	M16×P2.0	24			16,300
32M16-12T3C	●	3										


● Standard Stock

Maximum number of revolutions

Set the number of revolutions per minute within the recommended cutting speed specified by the workpiece on Page 12.

Do not use the end mill or cutter at the maximum revolution or higher since the centrifugal force may cause chips and parts to scatter even under no load.

BT Arbor for Modular (for exchangeable head/two face contact)




Dimensions

Description	Stock	Dimensions (mm)				Coolant hole	Arbor (Two-face clamping)	Applicable End Mill (Head)
		LF	BD	DCONWS	CRKS			
BT30K- M10-45	●	45	18.7	10.5	M10×P1.5	Yes	BT30	MA90-...M10-..
M12-45	●	45	23	12.5	M12×P1.75			MA90-...M12-..
BT40K- M10-60	●	60	18.7	10.5	M10×P1.5	Yes	BT40	MA90-...M10-..
M12-55	●	55	23	12.5	M12×P1.75			MA90-...M12-..
M16-65	●	65	30	17	M16×P2.0			MA90-...M16-..

● Standard Stock

BT Arbor for Modular (for exchangeable head/two face contact)

Actual End Mill Depth



Arbor description	Applicable End Mill (Head)			Actual End Mill Depth(mm)
	Description	Cutting Dia. (mm)	Dimensions (mm)	LUX
		DC	LF	
BT30K- M10-45	MA90-20M10-...	20	30	36.8
	MA90-25M12-...	25	35	42.8
BT40K- M10-60	MA90-20M10-...	20	30	38.7
	MA90-25M12-...	25	35	44.6
	MA90-32M16-...	32	40	51.2

Applicable Insert

Shape	Description	Dimensions (mm)						MEGACOAT (PVD coating)				CVD Coating	
		W1	S	D1	INSL	BS	RE	PR1825	PR1835	PR1810	PR015S	CA6535	
		Usage Classification: <ul style="list-style-type: none"> P: Carbon steel/Alloy steel (★), Mold Steel (★) M: Austenitic (★), Martensitic (☆), Stainless steel (Precipitation hardening system: ★) K: Gray cast iron (★), Ductile cast iron (★) S: Heat-resistant alloys (☆), Titanium alloy (★) H: Hardened material (★) ★: 1st recommendation, ☆: 2nd recommendation											
General Purpose (G-class)	LOGU 090404ER-GM	4.3	6.77	3.33	8.89	1.29	0.4	●	●	●	-	●	
	LOGU 090408ER-GM		6.71			0.90	0.8	●	●	●	-	●	
	LOGU 090412ER-GM		6.65			0.49	1.2	●	●	●	-	●	
	LOGU 090416ER-GM		6.59			0.10	1.6	●	●	●	-	●	
Low Cutting Force (G-class)	LOGU 090404ER-SM	4.3	6.77	3.33	8.89	1.29	0.4	●	●	-	-	●	
	LOGU 090408ER-SM		6.71			0.89	0.8	●	●	-	-	●	
	LOGU 090412ER-SM		6.65			0.49	1.2	●	●	-	-	●	
	LOGU 090416ER-SM		6.59			0.10	1.6	●	●	-	-	●	
Tough Edge (G-class)	LOGU 090408ER-GH	4.3	6.71	3.33	8.89	0.90	0.8	●	●	●	●	-	
General Purpose (G-class)	LOGU 120604ER-GM	6.6	10.10	4.55	13.28	2.50	0.4	●	●	●	-	●	
	LOGU 120608ER-GM		10.04			13.28	2.14	0.8	●	●	●	-	●
	LOGU 120612ER-GM		9.97			13.28	1.79	1.2	●	●	●	-	●
	LOGU 120616ER-GM		9.92			13.28	1.44	1.6	●	●	●	-	●
	LOGU 120620ER-GM		9.85			13.28	1.08	2.0	●	●	●	-	●
	LOGU 120624ER-GM		9.79			13.28	0.72	2.4	●	●	●	-	●
	LOGU 120630ER-GM		9.69			13.28	0.20	3.0	●	●	●	-	●
Low Cutting Force (G-class)	LOGU 120604ER-SM	6.6	10.10	4.55	13.28	2.50	0.4	●	●	-	-	●	
	LOGU 120608ER-SM		10.04			13.28	2.14	0.8	●	●	-	-	●
	LOGU 120612ER-SM		9.97			13.28	1.79	1.2	●	●	-	-	●
	LOGU 120616ER-SM		9.92			13.28	1.44	1.6	●	●	-	-	●
	LOGU 120620ER-SM		9.85			13.28	1.08	2.0	●	●	-	-	●
	LOGU 120624ER-SM		9.79			13.28	0.72	2.4	●	●	-	-	●
	LOGU 120630ER-SM		9.69			13.28	0.20	3.0	●	●	-	-	●
Tough Edge (G-class)	LOGU 120608ER-GH	6.6	10.16	4.55	13.25	2.26	0.8	●	●	●	●	-	


●: Standard Stock

Recommended cutting conditions ★1st recommendation ☆2nd recommendation

Insert Shape	Workpiece Material	Toolholder Description and Feed rate (fz: mm/t)				Recommended Insert Grade (Cutting speed Vc: m/min)				
		09 Size (LOGU09...)		12 Size (LOGU12...)		MEGACOAT NANO EX			MEGACOAT HARD	CVD coating
		MA90-16~MA90-18	MA90-20~MA90-50 MA90-040~MA90-063	MA90-25~MA90-30	MA90-32~MA90-50 MA90-040~MA90-125	PR1825	PR1835	PR1810	PR015S	CA6535
General GM	Carbon steel (SxxC)	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.16	0.05 - 0.1 - 0.18	0.06 - 0.15 - 0.23	★ 120 - 180 - 250	☆ 120 - 180 - 250	-	-	-
	Alloy steel (SCM, etc.)	0.05 - 0.08 - 0.12	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.16	0.06 - 0.13 - 0.2	★ 100 - 160 - 220	☆ 100 - 160 - 220	-	-	-
	Mold steel (SKD, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	★ 80 - 140 - 180	☆ 80 - 140 - 180	-	-	-
	Austenitic stainless steel (SUS 304, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	☆ 100 - 160 - 200	★ 100 - 160 - 200	-	-	-
	Martensitic stainless steel (SUS 403, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	-	☆ 150 - 200 - 250	-	-	★ 180 - 240 - 300
	Precipitation hardened stainless steel (SUS 630, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	-	★ 90 - 120 - 150	-	-	-
	Grey cast iron (FC)	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.16	0.05 - 0.1 - 0.18	0.06 - 0.15 - 0.23	-	-	☆ 120 - 180 - 250	-	-
	Ductile cast iron (FCD)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	-	-	☆ 100 - 150 - 200	-	-
	Ni-based heat resistant alloys	0.05 - 0.06 - 0.08	0.05 - 0.08 - 0.1	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.15	-	-	-	-	★ 20 - 30 - 50
	Titanium alloy (Ti-6Al-4V)	0.05 - 0.08 - 0.1	0.05 - 0.09 - 0.12	0.05 - 0.09 - 0.12	0.06 - 0.1 - 0.15	-	☆ 30 - 50 - 70	-	-	-
Low Cutting Force SM	Carbon steel (SxxC)	0.05 - 0.08 - 0.11	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.14	0.06 - 0.1 - 0.18	★ 120 - 180 - 250	☆ 120 - 180 - 250	-	-	-
	Alloy steel (SCM, etc.)	0.05 - 0.07 - 0.1	0.05 - 0.08 - 0.12	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.14	★ 100 - 160 - 220	☆ 100 - 160 - 220	-	-	-
	Mold steel (SKD, etc.)	0.05 - 0.07 - 0.1	0.05 - 0.08 - 0.1	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.14	★ 80 - 140 - 180	☆ 80 - 140 - 180	-	-	-
	Austenitic stainless steel (SUS304, etc.)	0.05 - 0.08 - 0.11	0.05 - 0.08 - 0.12	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.14	☆ 100 - 160 - 200	★ 100 - 160 - 200	-	-	-
	Martensitic stainless steel (SUS403, etc.)	0.05 - 0.08 - 0.11	0.05 - 0.08 - 0.12	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.14	-	☆ 150 - 200 - 250	-	-	★ 180 - 240 - 300
	Precipitation hardened stainless steel (SUS630, etc.)	0.05 - 0.08 - 0.11	0.05 - 0.08 - 0.12	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.14	-	★ 90 - 120 - 150	-	-	-
	Ni-based heat resistant alloys	0.05 - 0.06 - 0.08	0.05 - 0.08 - 0.1	0.05 - 0.08 - 0.1	0.06 - 0.08 - 0.12	-	-	-	-	★ 20 - 30 - 50
	Titanium alloy (Ti-6 Al-4V)	0.05 - 0.08 - 0.1	0.05 - 0.08 - 0.12	0.05 - 0.08 - 0.12	0.06 - 0.09 - 0.12	-	★ 30 - 50 - 70	-	-	-
Tough Edge GH	Carbon steel (SxxC)	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.16	0.05 - 0.1 - 0.18	0.06 - 0.15 - 0.23	★ 120 - 180 - 250	☆ 120 - 180 - 250	-	-	-
	Alloy steel (SCM, etc.)	0.05 - 0.08 - 0.12	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.16	0.06 - 0.13 - 0.2	★ 100 - 160 - 220	☆ 100 - 160 - 220	-	-	-
	Mold steel (SKD, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	★ 80 - 140 - 180	☆ 80 - 140 - 180	-	-	-
	Austenitic stainless steel (SUS304, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	☆ 100 - 160 - 200	☆ 100 - 160 - 200	-	-	-
	Martensitic stainless steel (SUS403, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	-	☆ 150 - 200 - 250	-	-	-
	Precipitation hardened stainless steel (SUS630, etc.)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	-	☆ 90 - 120 - 150	-	-	-
	Grey cast iron (FC)	0.05 - 0.1 - 0.14	0.05 - 0.1 - 0.16	0.05 - 0.1 - 0.18	0.06 - 0.15 - 0.23	-	-	★ 120 - 180 - 250	-	-
	Ductile cast iron (FCD)	0.05 - 0.08 - 0.1	0.05 - 0.1 - 0.12	0.05 - 0.1 - 0.14	0.06 - 0.12 - 0.18	-	-	★ 100 - 150 - 200	-	-
	Ni-based heat resistant alloys	0.05 - 0.06 - 0.08	0.05 - 0.08 - 0.1	0.05 - 0.08 - 0.12	0.06 - 0.1 - 0.15	-	-	-	-	-
	Titanium alloy (Ti-6 Al-4V)	0.05 - 0.08 - 0.1	0.05 - 0.09 - 0.12	0.05 - 0.09 - 0.12	0.06 - 0.1 - 0.15	-	☆ 30 - 50 - 70	-	-	-

The number in bold font is recommended starting conditions. Adjust the cutting speed and the feed rate within the above conditions according to the actual machining situation. Machining with coolant is recommended for Ni-base heat-resistant alloys and titanium alloys. When choosing wet machining for other workpieces, reduce the cutting speed to 70% or less. Face milling does not recommend slotting or pocketing. We recommend setting the ae to 75% or less. We recommend the small number insert type for ae of 30% or more. Working above recommended conditions or long-term use can damage the screws. It is recommended to replace the screws regularly.


Cutting Performance



09 Size (LOGU09...) Machining for Steel (Dry)


Cutting Dia. DC : $\phi 16 \sim \phi 18$

ae/DC



Cutting Dia. DC : $\phi 20 \sim \phi 63$

ae/DC




For other workpiece material, set ap and fz appropriately for each ae.

12 Size (LOGU12...) Machining for Steel (Dry)


Cutting Dia. DC : $\phi 25 \sim \phi 30$

ae/DC



Cutting Dia. DC : $\phi 32 \sim \phi 125$

ae/DC



For other workpiece material, set ap and fz appropriately for each ae.

Case Studies

Brake parts FCD500

Vc = 135 m/min
 n = 535 min⁻¹
 ap x ae = 3.4 x 25 mm
 fz = 0.15 mm/t
 Vf = 560 mm/min
 Wet
 MA90-080R-12T7C-M
 LOGU120616ER-GM (PR1810)



Number of Workpieces

MA90
(7 inserts)

1,000 pcs

Tool life

x1.6

Competitor G
(7 inserts)

600 pcs

MA90 showed good cutting edge condition and stable machining. Achieved 1.6 times longer tool life.

(User evaluation)

Mold parts Stainless steel

Vc = 125 m/min
 n = 1,600 min⁻¹
 ap x ae = 1.0 x 25 mm
 fz = 0.12 mm/t
 Vf = 570 mm/min
 Dry
 MA90-25S20-09T3C
 LOGU090408ER-GM (PR1835)



Machining efficiency

MA90
(3 inserts)

Q = 14.5 cc/min

x1.5

Machining efficiency

Competitor H
(3 inserts)


Q = 9.5 cc/min

MA90 showed 1.5 times higher machining efficiency than its competitors. Improved tool life (3 to 4 pcs)

(User evaluation)

Notes

Applications



Ramping Reference Table

Description	Cutter Diameter DC (mm)	16	20	25	32	40	50
MA... - 09 - ...	Max. Ramping Angle RMPX	1.16°	0.97°	0.64°	0.4°	0.23°	0.11°
	tan RMPX	0.020	0.017	0.011	0.007	0.004	0.002
Description	Cutter Diameter DC (mm)	25	28	30	32	35	40
MA... - 12 - ...	Max. Ramping Angle RMPX	2°	1.7°	1.6°	1.5°	1.2°	1°
	tan RMPX	0.034	0.030	0.027	0.026	0.021	0.017


Decrease the angle of inclination when the chips extend longer.

Ramping Tips

Ramping angle should be under RMPX.
Reduce recommended feed rate by 70%

Formula for Min. Cutting Length (L) at Max. Ramping Angle

$$L = \frac{ap}{\tan RMPX}$$




Helical Milling Tips

For Helical milling, use between min. cutting dia. and max. cutting dia.


Exceeding max. cutting dia.

Center core remains after machining



Less than min. cutting dia.

Center core hits holder body




Units: mm

Description	Minimum cutting diameter øDh1	Maximum cutting diameter øDh2
MA... - 09 - ...	2×DC-4	2×DC-2
MA... - 12 - ...	2×DC-6	2×DC-2

For helical milling, use between min. cutting dia. and max. cutting dia..
The cutter direction should be counterclockwise (down cut) (see above).
Please machining in a safe environment as long chips may be produced.

Drilling Tips




Units: mm

Description	Maximum drilling depth Pd	Min. cutting length X for flat bottom surface
MA... - 09 - ...	0.25	DC-3
MA... - 12 - ...	0.5	DC-5

It is recommended to reduce feed by 25% of recommendation until the center core is removed when traversing after drilling.

Axial feed rate recommendation per revolution is $f = 0.1\text{mm/rev}$ or less when drilling.


Plunging Tips



Available for vertical milling (plunging)
Feed should be set within $fz = 0.1$ (mm/t) when plunging.

Units: mm

Description	Maximum width of cut (ae)
09 Size (LOGU09...)	2
12 Size (LOGU12...)	3



Tangential Cutter

***Safe. Rigid.
Quality Machining***

The information contained in this brochure is current as of March 2023.
Duplication or reproduction of any part of this brochure without approval is prohibited.

CP477 CAT/25T2303DNN
© 2023 KYOCERA Corporation